

Complete Fluid Handling Solutions for Sanitary & Ultra-Hygienic Markets

Air Operated Diaphragm Pumps

Centrifugal Pumps

Circumferential Piston Pumps

Rotary Lobe Pumps

Tubular Diaphragm Pumps

Flow Meters



wright flow
TECHNOLOGIES



SteriLobe: Heavy Duty, Low Shear Pumping Action with In-Line Cleanability


- EHEDG Certified CIP, SIP Capable
- 316L stainless steel construction
- Design for virtually pulse-free flow with minimal shear
- Front loading seals for minimum maintenance time
- Universal mounting and self draining capabilities
- These features have made this pump the Standard for demanding Pharmaceutical Applications

Capacity: to 1,014 USGPM (230 M³/Hr) **Pressure:** to 215 PSI (15 BAR)
Temperature: -4°F to +300°F (-30°C to +150°C)

Multipump: Economical, Low Shear Pumping Action with In-Line Cleanability

- Self draining design with CIP, SIP, or strip clean capabilities
- Robust, 316L stainless steel product-wetted construction
- Tri-lobe non-contacting rotors for smooth, low shear flow
- Universal mounting to facilitate self draining
- Dry running capability

Capacity: to 650 USGPM (148 M³/Hr) **Pressure:** to 175 PSI (12 BAR) **Temperature:** -22°F to +350°F (-29°C to +180°C)



Acculobe: Accurate, Filling and Dosing for Sanitary Applications



- Front-loading seal design for minimum maintenance time
- One-piece pump/gear case extends bearing and seal life
- Multi-lobe rotors standard for minimal pulsation and noise
- Non-galling rotors with reduced clearances available for very low viscosity liquids
- Ideal for dosing & lab applications.

Capacity: 0 to 9.2 USGPM (35 Liters/Min) **Pressure:** to 175 PSI (12 BAR) **Temperature:** -40°F to +300°F (-40°C to +150°C)

Concept SQ: Probably the Cleanest Pump in the World

- E.H.E.D.G. Certified for CIP & Certified for SIP
- No Rotor Retainers in pump head
- Available with Steam aseptic barriers
- Self draining design
- Aseptic Cover Joints

Capacity: to 484 USGPM (110M³/Hr) **Pressure:** to 220 PSI (15 BAR) **Temperature:** -300°F (150°C)



RTP: Designed Specifically for Road Transport Applications

- Compact & lightweight
- Bi-directional operation enables emptying hoses
- Optional with high efficiency rotors
- Ultra Hygienic CIP / SIP Design
- Front loading seals of minimum maintenance time

Capacity: to 339 USGPM (77M³/Hr) **Pressure:** to 175 PSI (12 BAR)
Temperature: -300°F (150°C)

Hydratube Seal Less Metering Pump: Designed for low shear applications where CIP & SIP are required

- Low shear hydraulic action protects products
- CIP & SIP design virtually eliminates contamination risks
- Excellent metering accuracy, ±1% over full operating range
- 0-100% flow range adjustment to maximum pressure with economical motor drive
- Hydraulic medium can be any neutral non-contaminating liquid

Capacity: to 124 USGPH (468 LPH) **Pressure:** to 150 PSI (10 BAR) **Viscosity:** to 6,800 SSU (1,500 cSt)
Temperature: 0°F to +266°F (-18°C to +130°C)





TRA[®] 10: The Circumferential Piston Pump for Shear-Sensitive Fluids

- Wright 808[®] non-galling, nickel-based alloy rotors
- Helical timing gears
- One-piece 316L stainless steel shaft*, One-piece 17-4 PH high strength steel shaft**
- Vertical or horizontal porting with 4-way case mounting
- Stainless steel bearing retainers
- Drop-in replacement for Waukesha[®] U1

Capacity: to 450 USGPM (102 M³/Hr) **Pressure:** to 200 PSI (14 BAR)***
Temperature: -40°F to +300°F (-40°C to +150°C)

* Standard on sizes 0600, 0150, and 0180. ** Standard on sizes 0300, 0450, 0600, 1300, 2200, and 3200.***Model 0450 to 400 PSI (27 BAR)



TRA[®] 20: The Circumferential Piston Pump That Delivers Under Pressure Every Time

- CIP Capabilities
- Helical timing gears
- One-piece 316L stainless steel shaft*
- One-piece 17-4 PH high strength steel shaft**
- Wright 808[®] non-galling, nickel-based alloy rotors
- Vertical or horizontal porting with 4-way case mounting
- Drop-in replacement for Waukesha[®] U2

Capacity: to 310 USGPM (70 M³/Hr) **Pressure:** to 500 PSI (34 BAR)
Temperature: -40°F to +300°F (-40°C to +150°C)

* Standard on sizes 0600, 0150, and 0180. ** Standard on sizes 0300, 0450, 0600, 1300, 1800, 2100, and 2200.



TRA[®] 400: The Centrifugal Choice For High Purity Transfer

- Machined from solid bar and plate
- -Low ferrite eliminates rouge in pure water systems
- Exclusive SoftSterile[™] seal flushing system (Patented)
- Exclusive true Zero-Dead-Leg casing drain (Patented)
- Comprehensive IQ supporting documentation
- USP class VI elastomers


Capacity: to 300 USGPM (70 M³/Hr) **Pressure:** to 135 PSI (9.3 BAR) **Viscosity:** to 2,700 SSU (660 cSt)
Temperature: -20°F to +380°F (-29°C to +195°C)



TRA[®] 500: The Centrifugal Choice For High Volume Sanitary Applications

- Corrosion resistant stainless steel flange adapters
- No-weld inlet and outlet clamp connections
- One size mechanical seal fits all - through 30 Hp=22kW
- Integral inlet/outlet in housing provides ease of service
- Polished exterior surfaces (no 'as cast' surfaces on pump head)
- Dimensionally interchangeable with Fristam[®] FPX[®] and FPR[®] Models

Capacity: to 900 USGPM (210 M³/Hr) **Pressure:** to 190 PSI (13 BAR) **Viscosity:** to 2,700 SSU (600 cSt)
Temperature: -20°F to +380°F (-29°C to +195°C)



Flow Meters: Highly Accurate Flow Measurement Used in Process Control, Batching Or Blending

Steriblade - Turbine

- Accuracies capable +/-0.5%, repeatable to 0.1%
- CIP with remote display
- Available in SS 304, 316
- If damaged, Blade cartridge can be quickly replaced for minimum downtime
- Available as non-3A lower cost option

Capacity: to 1,250 USGPM (284 M³/Hr)
Viscosity: to 250 cSt
Temperature: -450°F to +750°F (-268°C to +399°C)

MagWright - Magnetic

- Accuracies capable +/-0.2%, repeatable to 0.1%
- CIP with remote display
- PTFE lined with 316SS electrodes
- Obstruction-less flow for little or no pressure loss
- Available as non-3A lower cost option

Capacity: to 0.375-4542 lpm (0.1-1200 GPM)
Temperature: -149°C (300°F) Remote Conv.





T-Series AODD: Food grade FDA Material Compliant Range


- FDA compliant materials of construction
- Transfers thin liquids with 90% food particulates
- Self-priming, dry-run capabilities
- Available sizes 1½", 2", 2½", 3" and 2½" Flapper for handling 2" Solids
- Made in USA

Capacity: to 250 USGPM (57 M³/Hr) **Pressure:** to 125 PSI (8.6 BAR) **Viscosity:** to 250,000 SSU (55,000 cSt)
Temperature: -10°F to +212°F (-23°C to +100°C)

V-Series AODD: For Sanitary Processing that Require Easy Cleaning Capabilities & 3A

- CIP Capabilities
- Easy clean tri-clamp connections and wing-nut clamp bands for quick assemble and disassemble
- 316L stainless steel construction with 180°C Rotating Pump stand
- Gently handles solids up to 5/8" (.625) in diameter
- Leak Detection system optional for 3A compliance
- Available sizes 1½" & 2"
- Made in USA

Capacity: to 180 USGPM (680 LPM) **Pressure:** to 100 PSI (6.9 BAR) **Viscosity:** to 250,000 SSU (55,000 cSt)
Temperature: -10°F to +212°F (-23°C to +100°C)



Dominator AODD: For Sanitary Processing that Requires Easy Cleaning Capabilities

- CIP up to 130°C
- Easy clean tri-clamp connections and wing nut clamp bands
- Stainless Steel S1S 2343
- Sizes ½", 1", 2"
- Made in Sweden

Capacity: to 79 USGPM (300LPM) **Pressure:** to 145 PSI (10 BAR) **Temperature:** 212°F (100°C)

B-Series AODD: Premier EHEDG Range

- EHEDG certified for highest cleanliness standards (CIP)
- 316 Stainless Steel
- Tri-clamp connections and optional 180°C Rotation to facilitate cleaning
- Sizes ½", 1", 2"
- Made in England

Capacity: to 125 USGPM (476 LPM) **Pressure:** to 125 PSI (8.6 BAR)
Temperature: Determined by elastometers.



For more information, contact your local authorized Wright Flow Technologies Distributor or contact us at:



Wright Flow Technologies, Inc.

S84 W18693 Enterprise Drive
Muskego, WI 53150
Phone: (262) 679-8000
Fax: (262) 679-2026
Email: info.wright@idexcorp.com

Wright Flow Technologies Ltd.

Highfield Industrial Estate,
Edison Road Eastbourne
East Sussex, United Kingdom, BN23 6PT
Phone: +44 1323 509211 Fax: +44 1323 507306
E-mail: jinfo@idexcorp.com

Visit us online at:

www.wrightflowtechnologies.com
www.johnsonpump.com
www.wrightpump.com

ASIA-PACIFIC

China	Beijing	- Phone: +86-10-6522-7567/27	Fax: +86-10-6522-7563
	Chengdu	- Phone: +86-28-86767458	Fax: +86-28-86767468
	Guangzhou	- Phone: +86-20-3886-6156	Fax: +86-20-3886-2776
	Shanghai	- Phone: +86-21-5241 5599	Fax: +86-21-5241 8339
South Asia	India	- Phone: +91-22-6678-0048/53	Fax: +91-22-6678-0055
ASEAN	Singapore	- Phone: +65-6763-6633	Fax: +65-6764-4020
Middle East	Dubai	- Phone: +971-4-225-7978	Fax: +971-4-225-9796
Oceania		- Phone: +61-(0) 4577-4534	Fax: +61-(0) 448-480-640

LATIN AMERICA

Brazil	- Phone: +55-19-3871-3500	Fax: +55-19-3871-6400
Caribbean	- Phone: +1 (305) 740-3365	Fax: +1 (305) 740-3372
Cono Norte/Central America	- Phone: +57 1 648 2761	Fax: +57 1 274 3453
Cono Sur	- Phone: +1 (803) 234-3004	Fax: +1 (803) 216-7670
Mexico	- Phone: +52 55 5255-1357	Fax: +52 55 5255-1356

